

Sunrays

Adjustable COB Downlighter

Super **Bright** | Life **50000 Hrs** | Higher **Efficiency**

IS 15855
(Part 2/Sec 13)



R-41056626



Code : ELDL 333

Power	Dimension (mm)	Cutout (mm)	PF	CRI	Lumens	Beaming Angle
3W	Ø66*H30	Ø55	0.6	>80	240 lm	30°
6W	Ø81*H40	Ø65	0.6	>80	480 lm	30°
9W	Ø90*H50	Ø75	0.6	>80	720 lm	30°
16W	Ø110*H65	Ø90	0.9	>80	1280 lm	30°
24W	Ø145*H84	Ø135	0.9	>80	1920 lm	45°
30W	Ø145*H84	Ø135	0.9	>80	2400 lm	45°

CCT : 3000K / 6000K



Code : SEB 958

Power	Dimension (mm)	Cutout (mm)	PF	Lumens	Beaming Angle
5W	Ø90xH60	Ø75	0.9	450 lm	45°
10W	Ø110xH75	Ø95	0.9	900 lm	45°
15W	Ø140xH90	Ø120	0.9	1350 lm	45°
20W	Ø98xH55	Ø120	0.9	1800 lm	45°

CCT : 3000K / 4000K / 6000K

**SAVE
80%
ENERGY**

**Low-carbon
life**
Share the low-carbon life
Build a green home



Environmental friendly
aesthetically designed, decorative
recess mounted down light for
low ceiling height applications.