

Premium

LED Wall Light (T5)

- One equals to two traditional T5 tube in the same size.
- Maximum efficiency and minimum glare • High-tech optical design
- Quick installation and easy maintenance with middle-out wire.
- Batten integrated T5 led light can greatly save labour cost
- No UV, No Lead, No Mercury

IS 10322
(Part 5/Sec 1)



R-41059978

Beaming Angle **120°** | CRI **Ra > 70**
PF **0.9** | Life **50,000 Hrs**



| Power(W) | CODE | CCT | Lumens(Lm) | Input VAC | Driver | Size(mm) |
|----------|----------|-----------------|------------|-----------|------------------------------|------------|
| 5W | ELT5 555 | 3000/4000/6500K | 475 | 100-300V | 2.5kV Surge/N on Isolated | 37x21x290 |
| 9W | ELT5 555 | 3000/4000/6500K | 855 | 100-300V | | 37x21x570 |
| 13W | ELT5 555 | 3000/4000/6500K | 1235 | 100-300V | | 37x21x870 |
| 18W | ELT5 555 | 3000/4000/6500K | 1710 | 100-300V | | 37x21x1180 |
| 20W | ELT5 555 | 3000/4000/6500K | 1900 | 100-300V | | 37x21x1180 |

| Power(W) | CODE | CCT | Lumens(Lm) | Input VAC | Driver | Size(mm) |
|----------|----------|-----------------|------------|-----------|------------------------------|------------|
| 7W | ELT5 556 | 3000/4000/6500K | 665 | 100-300V | 2.5kV Surge/N on Isolated | 35x30x300 |
| 14W | ELT5 556 | 3000/4000/6500K | 1330 | 100-300V | | 35x30x580 |
| 20W | ELT5 556 | 3000/4000/6500K | 1990 | 100-300V | | 35x30x890 |
| 28W | ELT5 556 | 3000/4000/6500K | 2660 | 150-300V | | 35x30x1190 |

Temperature Characteristic T-ambient 25°

Temperature

Operating -20~+40°C
Storage -40~+85°C

Humidity

Operating -20~+40°C
Storage -20~+40°C

Electrical Characteristic

Input Voltage : AC100~300V 50/60Hz



**SAVE
80%
ENERGY**

